



Rugged Wearable

Unleash new possibilities







































Hands-free operation

Performing a scanning operation is easier than lifting a finger, literally. With this new rugged wearable, not only work efficiency is improved, but the user comfort experience is also greatly enhanced

Optional ring scanner

 $\ensuremath{\mathsf{1D}}$ and $\ensuremath{\mathsf{2D}}$ scan engine, both with wired and wireless option are available

Fast data connectivity

Supports 4G and 3G cellular radio, and 802.11a /b/g/n WiFi, and Bluetooth

Rugged design and reliability

The U2 is drop tested with 1.5m and the sealing is tested with IP65 standard



http://www.urovo.com/en

UROVO U2 Specification

Basic Characteristics	0.S	Android 5.1
	CPU	Quad-Core 1.2GHz
	Display	4.0 inch TFT-LCD WVGA (480×800) color screen
	Panel	Support Multiple finger touch, gloves touch.
	RAM	1GB/2GB
	ROM	8GB/16GB
	Dimensions	118mm×91mm×33mm
	Weight	273g (Included battery and wristband)
	Buttons	Context Button, Home Button, Back Button, 2 User definable buttons (F1, F2) , Button, power button
Power	Main Battery	Rechargeable 3.8V 2850 mAh
	Charging time	No more than 4 hours
	RTC Battery	Real time clock battery
Radio Communication	Wi-Fi	802.11 a/b/g/n wireless communication
	Bluetooth	Bluetooth 4.0 HS low energy
	Chinese version	4G TDD-LTE:Band 38/39/40/41; FDD-LTE:Band 1/3 3G UMTS(WCDMA)/HSPA+/DC-HSDPA:850/900/2100MHz 2G GSM/EDGE:850/900/1800MHz
	International Version	4G FDD-LTE:Band1/2/3/4/5/7/8/20/28A/28B 3G UMTS(WCDMA)/HSPA+/DC-HSDPA:850/900/1900/2100MHz 2G GSM/EDGE:850/900/1800/1900MHz
Expansion and peripherals	Camera	8MP camera with LED flash and auto-focus function; Support camera scanning
	GPS	GPS, A-GPS, BDS
	Slot	Micro SD/TF, Micro SIM
	Interfaces	3.5mm Audio port, Magnetic pogo pin (With USB and charging functions, Support wired scanner)
Accessories	Audio	Loadspeaker, Microphone
	Standard Accessories	Power adaptor, USB-Magnetic pogo pin data cable, Instructions, Wristband
	Optional Accessories	Battery charger, ring scanner
User Environment	Operating Temperature	-10~50°C
	Storage Temperature	-20~70°C
	Humidity	5% ~ 95% (non condensing)
	Drop Durability	1.5m







Urovo Technology Corporation Limited